



Taxi Screen



PRODUCT SPECIFICATION

Modules	Item	Mobile					
	Model	TM960x320-2A	TM960x320-2.5A	TM960x320-3A	TM960x320-4A	TM960x320-5A	
	Pixel Pitch (mm)	2	2.5	3.076	4	5	
	Pixel Density (dot/m²)	250000	160000	105625	62500	40,000	
	LED Type	SMD1415	SMD1415	SMD1415	SMD1921	SMD1921	
	Module Size (W x H)mm	320 x 160	320 x 160	320 x 160	320 x 160	320 x 160	
	Module Resolution (W x H)	160 x 80	128 x 64	104 x 52	80 x 40	64 x 32	
	Module Weight (Kg)	0.32	0.32	0.32	0.28	0.28	
	Power Consumption per Module (W)	35~40					
Main technical Parameters	Driver Mode (Scan)	1/20	1/16	1/13	1/8	1/8	
	Brightness (cd/m²)	4000~4500					
	Grey Scale (bits)	14	14	14	14	14	
	Refresh Rate (Hz)	≥3840					
	Unit Size (W x H x D)mm	1046 x 400 x 139					
	Display Size (W x H)	960 x 320					
	Display Resolution (W x H)	480 x 160	384 x 128	312 x 104	240 x 80	192 x 64	
	Unit Weight (Kg/PC)	21 (additional packaging material 25KG)					
	Max Power Consumption (W/Sets)	420~480					
	Average Power consumption (W/m²)	126~144					
	Viewing Angle	Degree: H	120°				
		Degree: V	120°				
	Mini View Distance (m)	2	2.5	3	4	5	
	Use Temperature(°C)	Operating	-10°C~40°C/14°F~104°F				
		Storage	-20°C~50°C/-4°F~122 °F				
	Input Voltage	DC 8~20V					
	Failure Rate	<1/50,000					
	Control Type	USB \ Network \ Wifi & 4G optional					
	Life Time (hrs)	50,000					
IP Level	IP 65						



Shenzhen office



Email: Ben@lan-display.com



Contact: +8618681485066



Add: B8 BuildingYijing Industrial area,Guangming,Shenzhen 518107



Delivery Box Screen



PRODUCT SPECIFICATION

Modules	Item	Mobile		
	Model	WM2.6	WM3	WM4
	Pixel Pitch (mm)	2.6/2.4	3	4
	Pixel Density (dot/m ²)	145125	111111	62500
	LED Type	SMD1921	SMD1921	SMD1921
	Display Size (W x H)mm	336 x 384	336 x 384	320 x 384
	Module Resolution (W x H)	128 x 160	112 x 128	80 x 96
	Module Weight (Kg)	0.65~0.7		
	Power Consumption per Module (W)	65~75		
Main technical Parameters	Driver Mode (Scan)	1/20	1/16	1/16
	Brightness (cd/m ²)	3500~4500		
	Grey Scale (bits)	14		
	Refresh Rate (Hz)	≥1920		
	Unit Size (W x H x D)mm	500 x 500 x 500		
	Display Size (W x H)	336 x 384 x 3 side	336 x 384 x 3 side	320 x 384 x 3 side
	Unit Weight (Kg/PC)	16 (additional packaging material 21KG)		
	Max Power Consumption (W/Sets)	195~225		
	Average Power consumption (W/m ²)	60~75		
	Viewing Angle	120°		
		120°		
	Mini View Distance (m)	2.6	3	4
	Use Temperature(°C)	-10°C~40°C/14°F~104°F		
		-20°C~50°C/-4°F~122 °F		
	Input Voltage	DC 9~36V		
	Failure Rate	<1/50,000		
	Control Type	Wifi Or 4G optional		
	Life Time (hrs)	50,000		
	IP Level	IP 65		

